



## Inokssan Civata

Spring lock washers for screws  
with cylindrical head



1.4310 / A 4

d	für Gewinde for thread	d min.	d <sub>1</sub> max.	h min.	s	1.4310	A 4	
3	M 3	3,1	5,6	2	1	0,75	0,80	1000
3,5	M 3,5	3,6	6,1	2	1	2,00	2,20	1000
4	M 4	4,1	7	2,4	1,2	1,00	1,15	1000
5	M 5	5,1	8,8	3,2	1,6	1,65	1,80	1000
6	M 6	6,1	9,9	3,2	1,6	2,05	2,35	1000
8	M 8	8,1	12,7	4	2	3,90	4,50	1000
10	M 10	10,2	16	5	2,5	6,90	8,05	1000
12	M 12	12,2	18	5	2,5	8,35	9,75	500
14	M 14	14,2	21,1	6	3	12,90	15,20	500
16	M 16	16,2	24,4	7	3,5	20,00	23,60	250
18	M 18	18,2	26,4	7	3,5	21,70	25,70	250
20	M 20	20,2	30,6	9	4,5	39,20	46,60	250
22	M 22	22,5	32,9	9	4,5	43,20	51,10	100
24	M 24	24,5	35,9	10	5	59,80	71,00	100
27	M 27	27,5	38,9	10	5	74,10	86,40	100
30	M 30	30,5	44,1	12	6	110,00	129,00	100

Preise/Prices...100 Stück/pcs.

Bestellbeispiel/example for ordering: DIN 7980 - A 4 - 10

**\*DIN 7980 ersatzlos zurückgezogen, Artikel aber weiter lieferbar.  
Werkstoff A 4 mit reduzierter Federkraft gegenüber 1.4310.**

\*DIN 7980 withdrawn and not replaced, but article still available.  
Quality A 4 with reduced spring resistance to 1.4310.