


Inokssan Civata

Tapping screws, countersunk head, six lobe drive, type C (with cone point)



A 2

k	1,7	2,1	2,3	2,5	3	3,4	3,8
d1 max.	5,5	6,8	7,5	8,1	9,5	10,8	12,4
T-No.	T 8	T 10	T 15	T 20	T 25	T 25	T 30

d	2,9	3,5	3,9	4,2	4,8	5,5	6,3
	No. 4	No. 6	No. 7	No. 8	No. 10	No. 12	No. 14

l (mm)		2,9	3,5	3,9	4,2	4,8	5,5	6,3
9,5	3/8"	4,40	5,75	6,95	7,80	9,80		
13	1/2"	4,60	6,05	6,95	7,95	10,10	16,30	22,40
16	5/8"	5,10	6,40	7,40	8,80	10,90	17,50	18,90
19	3/4"	5,40	7,15	8,10	9,70	12,20	18,70	20,20
22	7/8"	9,00	8,80	9,95	10,90	14,00	20,60	22,20
25	1"	9,45	9,20	10,30	11,30	14,30	22,00	23,60
32	1 1/4"		10,50	12,20	14,00	18,20	25,70	28,30
38	1 1/2"			14,00	15,90	20,40	29,20	31,30
45	1 3/4"				23,00	26,60	34,70	37,30
50	2"				26,20	27,50	39,00	46,40
60	2 3/8"							60,10
		1000	1000	1000	1000	1000	1000	1000
				≥ 38	≥ 32	≥ 25	≥ 25	≥ 19
				500	500	500	500	500
					≥ 50	≥ 45	≥ 45	≥ 25
				200	200	200	200	200

Preise/Prices... 100 Stück/pcs.

Bestellbeispiel/example for ordering: DIN 7982 ISR - A 2 - 2,9 x 13