


Inokssan Civata

Prevailing torque type hexagon nuts, non-metallic insert, thin type



A 2 / A 4

d	s	e	m	m ₁	h	A 2	A 4	
M 2,5	5	5,50	2,3	1,5	3,5	24,20	37,30	200
M 3	5,5	6,01	2,4	1,65	4	13,40	24,90	500
M 4	7	7,66	2,9	2,2	5	10,80	22,20	500
M 5	8	8,79	3,2	2,75	5	11,40	22,60	500
M 6	10	11,05	4	3,3	6	13,70	28,80	500
M 8	13	14,38	5,5	4,4	8	23,00	40,10	500
M 10	17	18,9	6,5	5,5	10	48,80	82,30	500
M 12	19	21,1	8	6,6	12	68,50	132,00	200
M 14	22	24,49	9,5	7,7	14	147,00	242,00	200
M 16	24	26,75	10,5	8,8	16	182,00	253,00	100
M 18	27	29,56	13	9,9	18,5	245,00	370,00	50
M 20	30	32,95	14	11	20	310,00	431,00	50
M 22	32	35,05	15	12,2	22	463,00	728,00	25
M 24	36	39,55	15	13,2	24	513,00	779,00	25
M 27	41	45,02	17	14,8	27	777,00	1412,00	25
M 30	46	50,85	19	16,5	30	1063,00	2243,00	25
M 33	50	55,37	22	18,2	33	2924,00	3057,00	25
M 36	55	60,79	25	19,8	36	3226,00	3333,00	25

Preise/Prices...100 Stück/pcs.

Bestellbeispiel/example for ordering: DIN 985 - A 2 - M 4

Sicherungsmuttern auch in Vollmetall-Ausführung (DIN 980 / ISO 7042).

Self-locking nuts all-metal as well (DIN 980 / ISO 7042).